SHENZHEN SINDA TECHNOLOGY CO., LTD

Add:5th Floor, No.11 Building,Tongfuyu Industrial Zone, Xili Town, Nanshan District, Shenzhen,China

Tel: +86-(0)755-26734766 **Fax:** +86-(0)755-26498273 **Mobile:** 8613418941749

Website: www.gsmalarmsystems.com

E-mail: Maggie@sdph.com **MSN: sdphgsm_alarm**@hotmail.com **skype: gsm.alarm**

Picture	Model Number:G12	*Mainly used in House,office,Factory,etc.*

Includes
One Wireless door/window magnetic contact
One PIR sensor
Two remote controllers
One siren(More than 110DB)
One wireless keyboard
One AC adapter
One English user manual

Specification of main unit:
Output power: DC12V
Input power: AC110V to 220V,50Hz or 60 Hz
Working hours of standby Battery(DC8.4V): More than 15 hours
Wireless frequency for above accessories:315MHZ/433MHZ
Includes

Description and Main functions

1.Wavecome GSM module.

2.8 wireless zones(1 wireless SOS zone, 1 wireless fire alarm zone, and the other 6 wireless zones can be definded by user).

3.You can connect wireless emergency button, wireless PIR sensor, wireless door/window contact, wireless smoke detector, wireless gas leakage detector, wireless glass break sensor etc. Each wireless zone can match numberless wireless sensors.

4.Can Auto-dial 3 phone No. and send 3 SMS while alarming.

5. Arm/disarm by remote controller and SMS.

6.It's easy to operate.

7. Can connect with intercom. You can talk to the mainframe with intercom.

8. Switch to Backup rechargeable battery when power is failure or cut by intruder.

9.Wireless signal transmission, and don't fear for cutting line by the intruders.

10. Wireless Emergency function:you can press the button to alarm immediately in order to get help if in emergencies.

11. Can send alarm signals to monitoring center through GSM network, such as the police station.

G12E GSM900/1800MHZ

G12EA GSM850/1900MHZ

Packaging Method	Packaging Dimension and Weight	
1 set of G12 into one gift box	**Gift Box:**	G.W.:1.5kgs
5 gift boxes into one carton.		Size:290(L)*270(W)* 85(H) mm
	Carton:	G.W.:8.0kgs
Frequency 850/1900mhz		Size: 445(L)*305 x 290 (H)mm

Support language: Chinese, English, Spainish, French, Russia

Picture	Model Number:G10 *Mainly used in House,office,Factory,etc.*
	Description and Main functions
Includes:	**1.Wavecome GSM module**.
One alarm host (main unit)	2.8 Wireless zones (1 wireless SOS zone, 1 wireless fire alarm zone, the other 6 wireless zones can be defined by user), 1 external power failure alarm zone and 2 wired zones.
One Wireless door/window magnetic contact	3.You can connect wired & wireless PIR sensor, door/window contact, smoke detector, gas leakage detector, glass break sensor etc. Each wireless zone can match numberless wireless sensors.
One PIR sensor	4.You can record your voice in the mainframe in advance and will call you or the police and play the voice while alarming.
Two remote controllers	5.Can send **SMS** to 3 mobile phone No. and Auto-dial 3 phone No. while alarming.
One siren(More than 110DB)	6.You can call the mainframe any time and listen what happened in the alarm area.
One wireless keyboard	7.You can arm/disarm and program the system by wireless keyboard, **SMS** or **phone**
One AC adapter	8. Report the alarm zone & type by **SMS** or voice and can be remote controlled by SMS and telephone.
One English user manual	9. Modify name of wireless zones and check the status of alarm mainframe by **SMS**.
Specification of main unit:	10.With voice reminder & password protection while the system is working.
Output power: DC12V	11. Can connect with intercom. You can talk to the mainframe with intercom.
Input power: AC110V to 220V,50HZ or 60 HZ	12. Switch to **Backup rechargeable battery** when the power is failure or cut by intruder and will send SMS and call you.If the power is recoverd, it will also send sms to you.
Working hours of standby Battery(DC8.4V): More than 10 hours	13.Wireless signal transmission, with Human voice guide and easy to use, and don't fear for cutting wire by the intruders.
Wireless frequency for above accessories: 315MHZ/433 MHZ	14. **Wireless Emergency function(24 hours zone)**:you can press the button to alarm immediately in order to get help if in emergencies.
	15.Can send alarm signals to monitoring center through GSM network, such as the police station

GSM frequency:				
G10E GSM900/1800MHZ				
G10EA GSM850/1900MHZ				
Packaging Method		**Packaging Dimension and Weight**		
1 set of G10 into one gift box		**Gift Box:**	G.W.1.5kgs	
5 gift boxes into one carton.			Size:290(L)*270(W)*85(H)mm	
		Carton:	G.W.8.0kgs	
			Size: 445(L)*305(W)*290 (H)mm	

Picture	Model Number:G11 *Mainly used in House,office,Factory,etc.*

Packing List:

Main unit

Magnetic Door Sensor

Two Wireless Remote Controls

Wireless Programming Keypad

PIR Motion Sensor

Mini Siren

12vDC Power Supply

Specification

a) GSM network frequency Standard:

900/1800MHZ, 850/1900MHZ optional

b) External power failure alarm:

Start-time: less than 1s

c) Alarm response time

Less than 10s (GSM in normality)

d) Power requirements:

AC 220V 50Hz

Standby lithium battery:

DC8.4V, 700/800mA, 4000mA optional

Standby battery working hours:

The alarm system is based on GSM network. With a GSM SIM card, it can be used wherever you want and no need to connect any wire, which is convenient and easy to install and use.

Main functions,

English language SMS and voice reminder, Spanish/Chinese/Russian for optional

With Partial arm function

With 2 wired zones, 12 wireless zones

With 3 Relay output to control your home appliances

With voice reminder when users operate the system

Work with external Microphone

Work with external speaker

Auto send SMS to remind users when GSM signal becomes weak

Work with wired & wireless PIR, door/window sensor, smoke/gas detector, glass break sensor etc.

Each wireless zone can match countless wireless sensors.

Users pre-record voice in the system and play the voice when system gives alarm

Send SMS to 3 mobile phones and auto-dial 3 phones to inform the users

Users use any phone to listen what is happening inside the house whenever & wherever.

Program and control the system by keyboard, remotes, SMS or phone remotely.

Send SMS to inform users which zone is alarming and will call users or the police after system is triggered

Use SMS to change the zone name & content

Use SMS to inquiry the system status wherever

With password protection, System will inform users when input wrong password for 3 times

Use any phone to call the system and anyone inside the house -can talk to you through a speaker.

Wireless Emergency function (24 hours zone)

With Backup rechargeable battery, system can work even when the power is failure or cut by intruder.

Send SMS to inform you when the power is failure or returns to normal.

Support monitoring center through GSM network to the police station or management centre

G11	NEW MODEL

more than 10 hours, 4000mA for over 3 days

e) Working conditions

Operating temperature: -20 to 60℃

Humidity: 20% to 95%

Wireless frequency 315/433MHZ

Support language: Chinese, English, Spainish, French, Russia

Picture

Includes:

One alarm host (main unit)
One wireless door/window magnetic contact
One wireless PIR sensor
Two remote controllers
One siren
One AC adapter
One English user manual

Specification of main unit:

Output power: DC12V

Input power: AC110V to 220V,50Hz or 60 Hz

Working hours of standby Battery(DC8.4V):

More than 15 hours

Wireless frequency for above accessories:

Model Number:G20

Mainly used in House,office,Factory,etc.

Description and Main functions

1. **WAVECOME GSM module**.
2. 10 wireless zones(1 wireless SOS zone, 1 wireless fire alarm zone, the other 6 wireless zones can be defined by user) and 1 external power failure alarm zone.
3. You can connect wireless emergency button, wireless PIR sensor, wireless door/window contact, wireless smoke detector, wireless gas leakage detector, wireless glass break sensor etc. Each wireless zone can match numberless wireless sensors.
4. With **LCD display** and **Control keyboard** on the mainframe.
5. Send **SMS** to 3 preset mobile phone numbers and Auto-dial 3 preset phone numbers while alarming.
6. You can call the mainframe any time and listen what happened in the alarm area.
7. With AC power status monitor function and password protection function
8. With fixed time arming/partial arming/disarming function
9. Control the alarm system by Control **keyboard ,remote control** or **SMS**.
10. Modify 8 wireless zones' name and check the system status by **SMS**.
11. Define the 8 wireless zones as arm/partial arm by control keyboard on the mainframe.
12. Switch to **Backup rechargeable battery** when the power is failure or cut by intruder.
13. Wireless Emergency function(24 hours zone):you can press the button to alarm immediately in order to get help if in emergencies.
14. Wireless signal transmission,and don't fear for cutting wire by the intruders.
15. Can send alarm signals to monitoring center through GSM network, such as the police station

GSM frequency:

G20E GSM900/1800MHZ

G20EA GSM850/1900MHZ — Need add 8 $

Packaging Method

1 set of G20 into one gift box

5 gift boxes into one carton.

Packaging Dimension and Weight

Gift Box: G.W.:1.2kgs
Size:290(L)*270(W)* 85(H) mm

Carton: G.W.:6.7kgs
Size: 445(L)*305 x 290 (H)mm

315MHZ/433MHZ	The quotation only for QTY 15sets or more
	Support language: Chinese, English, Spainish, French, Russia
Picture	**Model Number:G50B** ***Mainly used in House,office,Factory,etc.***
	Description and Main functions
	1. Color LCD screen, keypad with blue light
	2 .Maximum 24 wireless zones including 1 panic zones, 1 wireless fire zones, 22 wireless intruder zones.
	3. Maximum 2 wired zones
	4. 3 mobile phone numbers for SMS alarm.
	5. Recording voice
	6. Auto-arm time,Auto-disarm time and Auto-partial arm time available for programmed.
Standard packing list	7. Fixde code wireless accessories.
One main unit	8. SMS control & program
One wireless door/window magnetic contact	9. SMS modifies wireless zones name.
One wireless PIR sensor	10. One way communication available.
Two remote controllers	11. Handfree mobile phone
One black siren	12. Arm/disarm by keypad, remote controller, phone or SMS
One AC adapter	13. Call the main unit to listen in status whenever.
One English user manual	14. Entry delay alarm.
Specification:	15. Main unit with tamper switch.
* GSM frequency: 900/1800MHz (standard), 850/1900MHz (optional)	16. Internal MIC or external high sensitivity MIC (optional)
Working frequency of detectors:315M & 433M (optional)	17. Internal GSM antenna or external antenna(optional)
Alarm response time:Less than 8s (GSM in normality)	18. External power failure alarm.
The volume of siren: More than 110db	19. Working with monitoring center, such as police station
Power requirements: AC 110-220V 50Hz or 60Hz	New & Hot
Working power consumption：less than 3W	GSM frequency:
Standby battery：DC 12V/2A	**900/1800Mhz**
Operating temperature: -20℃ ~ 60℃	**850/1900Mhz**
Humidity: 20% to 95%	
	Support language: Chinese, English, Spainish, French, Russia

GSM MONITORING CENTER SOFTWARE

Picture	Model Number: PH-008 GSM Alarm Receiver
	Main functions;
	1.PH-008 GSM Alarm Receiver mainly finishes the functions that receive GSM SMS data and voice, and transfer them into standard RS232 serial port. It can submit the SMS data and voice to computer by connecting the RS232 serial port of GSM data module and computer.
	2.Use together with PH-BC110 Monitoring Center Software
	3.One GSM Alarm Receiver can manage numberless GSM alarm systems.
	4.It is better for one GSM alarm receiver to manage 200 to 500 GSM alarm devices.
	Model Number: PH-BC110 Monitoring Center Software,
	Main Functions;
	1.Record the customers detail communication information,such as address,telephone number,the family menbers...So if there is alarming,the operator can contact the family and show them the alarm messsage in time.
	2.When there is alarming,the system will read the customer's telephone No. loudly.So if it is at night,the sound can make the operator deal the easily and in time.
	3.With the Jpeg,jpg map.You can download the map from the web.And choose your own place, your own language.It make you easy to record the location of your customer.
	4.When it is alarm,the moniotr center will send out the map of your customer.So you can get the alarming location at once.At the same time,you can click the mark of your customer and deal the alarming message as the moniotr record.
	5.When it is alarming,you can press all the alarm message,including the address,telephone,name of your customer.
	6.With 3 passwords.The different managers can have the different rights to monitor the software center.It is very practical and safe.
	Package include: 1. Software and Softdog
	2. GSM Alarm Receiver